



EdgeConvert Specifications

	PRO SIGNAL HDMI TO AV CONVERTER	BLACKMAGIC BI-DIRECTIONAL SDI/HDMI CONVERTER	ANKER 6 PORT 5V USB-A CHARGING HUB
Description	This device can convert an HDMI digital HD signal into a composite video (CVBS) signal plus the L/R stereo audio signal. It allows digital devices to output to an ordinary TV or monitor which only receives analogue and other CVBS signals. (The composite video standard resolution is 480i & 576i and NTSC and PAL formats)	This device can convert SDI Video Input to HDMI Output and at the same time HDMI Input to SDI Output in different Video formats	This device provides the power to the Converters or 6 x USB-A devices from a single mains power plug
Connections	1 x HDMI Type A input 1 x CVBS Composite Video Output RCA socket 1 x Left Audio Output RCA Socket 1 x Right Audio Output RCA Socket	SDI Video Inputs 1 x SD, HD or 3G-SDI. SDI Video Outputs Automatically matches the HDMI video input HDMI Video Inputs HDMI Type A in. HDMI Outputs HDMI Type A out. Multi Rate Support Auto detection of SD or HD.	6 x USB-A ports
Video Standards	HDMI input 1080p/1080i/720p/576p/576i/480p CVBS output 480i/576i	SDI Video Standard 525i59.94 NTSC, 625i50 PAL HD Video Standard 720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p47.95, 1080p48, 1080p50, 1080p59.94, 1080p60 1080PsF25, 1080PsF29.97, 1080PsF30 1080i50, 1080i59.94, 1080i60 2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI, 2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI, 2Kp59.94 DCI, 2Kp60 DCI 2KPsF25 DCI, 2KPsF29.97 DCI, 2KPsF30 DCI HDMI Video Standards 525i29.97 NTSC, 625i25 PAL 720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p47.95, 1080p48, 1080p50, 1080p59.94, 1080p60 1080i50, 1080i59.94, 1080i60	N/A
Power	DC 5V to USB-A, consumption 3W	USB-C, consumption 2.5W	5V / 12A total output. AC 100-240V
Dimensions	73 x 61 x 23 mm	81 x 59 x 25 mm	99 x 70 x 26 mm